

-								
VT9000 DECT Wireless Headset Specifications								
	1			T	1	1	1	
		Р	roduct S	umma	ary			
		1.Comfortable with over-head						
		wearing	g style 2.Wideb	and a	udio f		entional	
		sound c			uulo I		eptional	
			3.Up to	6 hou	rs of ta	alk tim	ie, at	
			least 36 hours standby time					
		4.Battery Full charge in less than 3						
			hours 5.Extended range, 150m outdoor					
			and 30m in door					
			6.Volume and mute controls					
Terry		7.Multi-function button for easy						
		call handling 8.Seamlessly works with any standard desk phone						
		9.Noise-cancelling microphone					hone	
		10.Advanced hearing protection						
		with safetone™						
Specifications							I	
VT 9000 DECT HEADSET								
Operating environment:	0°C to +40°C; Up to 95% Rh non-condensing							
Call control:	Multi-function button support for answer call, end call,							
	docking operations also answer and end calls							
Volume control and microphone mute:	button controls on headset							
Visual indicator:	LED indicates call status, pairing status and other							
Audio indicatore	events							
Audio indicators:	Tones indicate incoming calls, low battery, volume level, microphone muting and other events.							
Sound quality:	DSP noise reduction; echo cancellation; tone control;							
	wideband and narrowband audio.							
Recharge:	While docked in the VT 9000 DECT Headset.							
Wireless standard:	(CAT - IQ) European DECT and U.S. DECT.							

DECT.			
DECT range:	For European DECT, up to 120 meters from VT 9000 DECT Headset base to headset.		
	For U.S. DECT, up to 350 feet from VT 9000 DECT		
	Headset base to headset.		
DECT frequencies:	US DECT: 1.92 - 1.93 Ghz.		
Deer nequencies.			
	EU DECT: 1.88 - 1.90 Ghz.		
Wearing-styles:	Headband		
Microphone boom arm style:	Long boom arm _o		
Speaker(s):	Wideband speaker.		
Microphone:	noise-cancelling microphone.		
VT 9000 DECT Base			
Dimensions:	97mm x 75 mm x 120 mm		
Wireless standard:	(CAT - IQ) European DECT and U.S.DECT.		
Operating environment:	-0°C to +40°C; Up to 95% Rh non-condensing.		
Recharge cradle:	Fits supplied VT 9000 DECT series headset.		
Desk Phone connections:	RJ-11 for handset, RJ-11 for phone body (or headset port), RJ-45 for AUX (for VT Link or lifter).		
Clear Dial tone switch and microphone	electromechanical switches. Clear dial tone switch and		
volume switch:	microphone volume level set manually.		
Headset Battery			
Battery type:	Lithium Ion-polymer.		
Battery capacity:	300 ma/h, typical.		
Battery talk time:	Up to 8 hours.		
Battery lifetime:	Minimum 1000 charge cycles.		
Battery standby time:	At least 36 hours.		
Operating temperature range:	-20°C to +60°C.		
Battery charge time:	20% charge in less than 20 minutes.		
	50% charge in less than 45 minutes.		
	Full charge in less than 3 hours.		
Battery shelf life:	headset battery holds charge for 6 months in the off		
	state, before recharge is required.		